




REPAINT Acrylic Flexible Paint

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** REPAINT
Acrylic Flexible Paint
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
Relevant uses: Liquid paint.
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**
MERCHANT UNION SL
Calle Colon 7 4ª Planta Of. 3 y 4
36202 Vigo-Spain
Tel: +34 986 29 19 08
Email: info@repaintweb.com
www.repaintweb.com
- 1.4 Emergency telephone number:** +34 986 29 19 08 (8:00-14:00)(15:30-17:30)

SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture:**
CLP Regulation (EC) n° 1272/2008:
Classification of this product has been carried out in accordance with CLP Regulation (EC) n° 1272/2008.
Eye Irrit. 2: Eye irritation, Category 2, H319
Skin Irrit. 2: Skin irritation, Category 2, H315
- 2.2 Label elements:**
CLP Regulation (EC) n° 1272/2008:
Danger
- 
- Hazard statements:**
Eye Irrit. 2: H319 - Causes serious eye irritation
Skin Irrit. 2: H315 - Causes skin irritation
Flam. Liq. 4 : H227 – Flammable Liquids
Asp. Tox. 1: H304 – Aspiration hazard
- Precautionary statements:**
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P280: Wear protective gloves/protective clothing/eye protection/face protection
P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P370+P378: In case of fire: Use ABC powder extinguisher to extinguish.
P501: Dispose of the contents/containers in accordance with the current legislation on waste treatment
P410+P412: Do not expose to sun light or temperatures higher than 50°C/122°F.
- Supplementary information:**
EUH066: Repeated exposure may cause skin dryness or cracking
EUH208: Contains Fatty acids, C18, unsatd., dimers, reaction products with N,N-dimethyl-1,3- propanediamine and 1,3-propanediamine. May produce an allergic reaction
- 2.3 Other hazards:**
Non-applicable

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS **








- 3.1 Substance:**
Non-applicable
- 3.2 Mixture:**

REPAINT
Acrylic Flexible Paint

** Changes with regards to the previous version

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS ** (continued)
Chemical description: Mixture composed of additives, aggregates, pigments, plasticizers and resins in solvents

Components: In accordance with Annex II of Regulation (EC) n°1907/2006 (point 3), the product contains:

| Identification | Chemical name/Classification | Concentration |
|--|---|---------------|
| CAS: 1330-20-7 EC: 215-535-7 Index: 601-022-00-9 REACH: 01-2119488216-32-XXXX | Xylene (mixture of isomers) ATP CLP00 | 25 - <50 % |
| | Regulation 1272/2008 Acute Tox. 4: H312+H332; Flam. Liq. 3: H226; Skin Irrit. 2: H315 - Warning  | |
| CAS: 108-10-1 EC: 203-550-1 Index: 606-004-00-4 REACH: 01-2119473980-30-XXXX | 4-methylpentan-2-one ATP CLP00 | 10 - <25 % |
| | Regulation 1272/2008 Acute Tox. 4: H332; Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H335; EUH066 - Danger  | |
| CAS: 78-93-3 EC: 201-159-0 Index: 606-002-00-3 REACH: 01-2119457290-43-XXXX | 2-butanone ATP CLP00 | 5 - <10 % |
| | Regulation 1272/2008 Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger  | |
| CAS: 100-41-4 EC: 202-849-4 Index: 601-023-00-4 REACH: 01-2119489370-35-XXXX | Ethylbenzene ATP ATP06 | 5 - <10 % |
| | Regulation 1272/2008 Acute Tox. 4: H332; Asp. Tox. 1: H304; Flam. Liq. 2: H225; STOT RE 2: H373 - Danger  | |
| CAS: 123-86-4 EC: 204-658-1 Index: 607-025-00-1 REACH: 01-2119485493-29-XXXX | Butyl Acetate ATP CLP00 | 25 - <50 % |
| | Regulation 1272/2008 Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Warning  | |
| CAS: 162627-17-0 EC: Non-applicable Index: Non-applicable REACH: Non-applicable | Fatty acids, C18, unsatd., dimers, reaction products with N,N-dimethyl-1,3-propanediamine and 1,3-propanediamine Self-classified | 0,25 - <0,5% |
| | Regulation 1272/2008 Skin Sens. 1: H317 - Warning  | |
| CAS: 111-76-2 EC: 203-905-0 Index: 603-014-00-0 REACH: 01-2119475108-36-XXXX | 2-butoxyethanol ATP CLP00 | <0,2 % |
| | Regulation 1272/2008 Acute Tox. 4: H302+H312+H332; Eye Irrit. 2: H319; Skin Irrit. 2: H315 - Warning  | |

** Changes with regards to the previous version

To obtain more information on the risk of the substances consult sections 8, 11, 12, 15 and 16.

SECTION 4: FIRST AID MEASURES
4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product is not classified as hazardous through inhalation, however, it is recommended in case of intoxication symptoms to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

- CONTINUED ON NEXT PAGE -



REPAINT Acrylic Flexible Paint

4.3 Indication of any immediate medical attention and special treatment needed: Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO₂). IT IS RECOMMENDED NOT to use tap water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and individual respiratory equipment. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inertization agent. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 94/9/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

- CONTINUED ON NEXT PAGE -

REPAINT
Acrylic Flexible Paint

SECTION 7: HANDLING AND STORAGE (continued)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C
Maximum Temp.: 30 °C
Maximum time: 24

Months B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the work environment

| Identification | | Environmental limits | |
|--|--------------|----------------------|-----------------------|
| Ethylbenzene CAS: 100-41-4 EC: 202-849-4 | IOELV (8h) | 100 ppm | 442 mg/m ³ |
| | IOELV (STEL) | 200 ppm | 884 mg/m ³ |
| | Year | 2015 | |
| Xylene (mixture of isomers) CAS: 1330-20-7 EC: 215-535-7 | IOELV (8h) | 50 ppm | 221 mg/m ³ |
| | IOELV (STEL) | 100 ppm | 442 mg/m ³ |
| | Year | 2015 | |
| 2-butoxyethanol CAS: 111-76-2 EC: 203-905-0 | IOELV (8h) | 20 ppm | 98 mg/m ³ |
| | IOELV (STEL) | 50 ppm | 246 mg/m ³ |
| | Year | 2015 | |
| 2-butanone CAS: 78-93-3 EC: 201-159-0 | IOELV (8h) | 200 ppm | 600 mg/m ³ |
| | IOELV (STEL) | 300 ppm | 900 mg/m ³ |
| | Year | 2015 | |
| 4-methylpentan-2-one CAS: 108-10-1 EC: 203-550-1 | IOELV (8h) | 20 ppm | 83 mg/m ³ |
| | IOELV (STEL) | 50 ppm | 208 mg/m ³ |
| | Year | 2015 | |

DNEL (Workers):

| Identification | | Short exposure | | Long exposure | |
|--|------------|-----------------------|-----------------------|-----------------------|-----------------------|
| | | Systemic | Local | Systemic | Local |
| Xylene (mixture of isomers) CAS: 1330-20-7 EC: 215-535-7 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 180 mg/kg | Non-applicable |
| | Inhalation | 289 mg/m ³ | 289 mg/m ³ | 77 mg/m ³ | Non-applicable |
| 4-methylpentan-2-one CAS: 108-10-1 EC: 203-550-1 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 11,8 mg/kg | Non-applicable |
| | Inhalation | 208 mg/m ³ | 208 mg/m ³ | 83 mg/m ³ | 83 mg/m ³ |
| 2-butanone CAS: 78-93-3 EC: 201-159-0 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 1161 mg/kg | Non-applicable |
| | Inhalation | Non-applicable | Non-applicable | 600 mg/m ³ | Non-applicable |
| Ethylbenzene CAS: 100-41-4 EC: 202-849-4 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 180 mg/kg | Non-applicable |
| | Inhalation | Non-applicable | 293 mg/m ³ | 77 mg/m ³ | Non-applicable |
| Butyl Acetate CAS: 123-86-4 EC: 204-658-1 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Inhalation | 960 mg/m ³ | 960 mg/m ³ | 480 mg/m ³ | 480 mg/m ³ |
| 2-butoxyethanol CAS: 111-76-2 EC: 203-905-0 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | 89 mg/kg | Non-applicable | 75 mg/kg | Non-applicable |
| | Inhalation | 663 mg/m ³ | 246 mg/m ³ | 98 mg/m ³ | Non-applicable |

DNEL (General population):

- CONTINUED ON NEXT PAGE -



REPAINT

Acrylic Flexible Paint

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

| Identification | | Short exposure | | Long exposure | |
|--|------------|-------------------------|-------------------------|--------------------------|--------------------------|
| | | Systemic | Local | Systemic | Local |
| Xylene (mixture of isomers) CAS: 1330-20-7 EC: 215-535-7 | Oral | Non-applicable | Non-applicable | 1,6 mg/kg | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 108 mg/kg | Non-applicable |
| | Inhalation | Non-applicable | Non-applicable | 14,8 mg/m ³ | Non-applicable |
| 4-methylpentan-2-one CAS: 108-10-1 EC: 203-550-1 | Oral | Non-applicable | Non-applicable | 4,2 mg/kg | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 4,2 mg/kg | Non-applicable |
| | Inhalation | Non-applicable | Non-applicable | 14,7 mg/m ³ | Non-applicable |
| 2-butanone CAS: 78-93-3 EC: 201-159-0 | Oral | Non-applicable | Non-applicable | 31 mg/kg | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 412 mg/kg | Non-applicable |
| | Inhalation | Non-applicable | Non-applicable | 106 mg/m ³ | Non-applicable |
| Ethylbenzene CAS: 100-41-4 EC: 202-849-4 | Oral | Non-applicable | Non-applicable | 1,6 mg/kg | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Inhalation | Non-applicable | Non-applicable | 15 mg/m ³ | Non-applicable |
| Butyl Acetate CAS: 123-86-4 EC: 204-658-1 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Inhalation | 859,7 mg/m ³ | 859,7 mg/m ³ | 102,34 mg/m ³ | 102,34 mg/m ³ |
| 2-butoxyethanol CAS: 111-76-2 EC: 203-905-0 | Oral | 13,4 mg/kg | Non-applicable | 3,2 mg/kg | Non-applicable |
| | Dermal | 44,5 mg/kg | Non-applicable | 38 mg/kg | Non-applicable |
| | Inhalation | 426 mg/m ³ | 123 mg/m ³ | 49 mg/m ³ | Non-applicable |

PNEC:

| Identification | | | | |
|--|--------------|----------------|-------------------------|----------------|
| Xylene (mixture of isomers) CAS: 1330-20-7 EC: 215-535-7 | STP | 6,58 mg/L | Fresh water | 0,327 mg/L |
| | Soil | 2,31 mg/kg | Marine water | 0,327 mg/L |
| | Intermittent | 0,327 mg/L | Sediment (Fresh water) | 12,46 mg/kg |
| | Oral | Non-applicable | Sediment (Marine water) | 12,46 mg/kg |
| 4-methylpentan-2-one CAS: 108-10-1 EC: 203-550-1 | STP | 27,5 mg/L | Fresh water | 0,6 mg/L |
| | Soil | 1,3 mg/kg | Marine water | 0,06 mg/L |
| | Intermittent | 1,5 mg/L | Sediment (Fresh water) | 8,27 mg/kg |
| | Oral | Non-applicable | Sediment (Marine water) | 0,83 mg/kg |
| 2-butanone CAS: 78-93-3 EC: 201-159-0 | STP | 709 mg/L | Fresh water | 55,8 mg/L |
| | Soil | 22,5 mg/kg | Marine water | 55,8 mg/L |
| | Intermittent | 55,8 mg/L | Sediment (Fresh water) | 284,74 mg/kg |
| | Oral | 1000 g/kg | Sediment (Marine water) | 284,7 mg/kg |
| Ethylbenzene CAS: 100-41-4 EC: 202-849-4 | STP | 9,6 mg/L | Fresh water | 0,1 mg/L |
| | Soil | 2,68 mg/kg | Marine water | 0,01 mg/L |
| | Intermittent | 0,1 mg/L | Sediment (Fresh water) | 13,7 mg/kg |
| | Oral | 20 g/kg | Sediment (Marine water) | 1,37 mg/kg |
| Butyl Acetate CAS: 123-86-4 EC: 204-658-1 | STP | 35,6 mg/L | Fresh water | 0,18 mg/L |
| | Soil | 0,0903 mg/kg | Marine water | 0,018 mg/L |
| | Intermittent | 0,36 mg/L | Sediment (Fresh water) | 0,981 mg/kg |
| | Oral | Non-applicable | Sediment (Marine water) | 0,0981 mg/kg |
| 2-butoxyethanol CAS: 111-76-2 EC: 203-905-0 | STP | 463 mg/L | Fresh water | 8,8 mg/L |
| | Soil | 3,13 mg/kg | Marine water | 0,88 mg/L |
| | Intermittent | 9,1 mg/L | Sediment (Fresh water) | 34,6 mg/kg |
| | Oral | 20 g/kg | Sediment (Marine water) | Non-applicable |

8.2 Exposure controls:

A.- General security and hygiene measures in the work place

As a preventative measure it is recommended to use basic Personal Protection Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.



- CONTINUED ON NEXT PAGE -





REPAINT Acrylic Flexible Paint

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

B.- Respiratory protection



| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|--|---------------------------|---|---------------------|--|
|  Compulsory use of face mask | Filter mask for particles |  | EN 149:2001+A1:2009 | Replace when an increase in resistance to breathing is observed. |

C.- Specific protection for the hands





| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|--|---|---|---|--|
|  Mandatory hand protection | NON-disposable chemical protective gloves |  | EN 374-1:2003 EN 374-3:2003/AC:2006 EN 420:2003+A1:2009 | The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin. |

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application



D.- Ocular and facial protection

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|---|-----------|--|---|---|
|  Mandatory face protection | Face mask |  | EN 166:2001 EN 167:2001 EN 168:2001 EN ISO 4007:2012 | Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. |

E.- Bodily protection

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|---|---|---|---|---|
|  Mandatory complete body protection | Disposable clothing for protection against chemical risks, with antistatic and fireproof properties |  | EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982-1:2004/A1:2010 EN ISO 6529:2001 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994 | For professional use only. Clean periodically according to the manufacturer's instructions. |
|  Mandatory foot protection | Safety footwear for protection against chemical risk, with antistatic and heat resistant properties |  | EN 13287:2008 EN ISO 20345:2011 EN 13832-1:2006 | Replace boots at any sign of deterioration. |

F.- Additional emergency measures

| Emergency measure | Standards | Emergency measure | Standards |
|---|--------------------------------|--|-------------------------------|
|  Emergency shower | ANSI Z358-1 ISO 3864-1:2002 |  Eyewash stations | DIN 12 899 ISO 3864-1:2002 |

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

| | |
|---------------------------|---------------------------------------|
| V.O.C. (Supply): | 63,02 % weight |
| V.O.C. density at 20 °C: | 598,64 kg/m ³ (598,64 g/L) |
| Average carbon number: | 6,96 |
| Average molecular weight: | 100,8 g/mol |

**REPAINT**
Acrylic Flexible Paint**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES****9.1 Information on basic physical and chemical properties:**

For complete information see the product datasheet.

Appearance:

| | |
|--------------------------|------------------|
| Physical state at 20 °C: | Liquid |
| Appearance: | Viscous |
| Color: | Various |
| Odor: | Solvent |
| Odour threshold: | Non-applicable * |

Volatility:

| | |
|--|-------------------|
| Boiling point at atmospheric pressure: | 120 °C |
| Vapour pressure at 20 °C: | 2700 Pa |
| Vapour pressure at 50 °C: | 11160 Pa (11 kPa) |
| Evaporation rate at 20 °C: | Non-applicable * |

Product description:

| | |
|--|-----------------------------|
| Density at 20 °C: | 930 - 970 kg/m ³ |
| Relative density at 20 °C: | 0,93 - 0,97 |
| Dynamic viscosity at 20 °C: | 457 - 461 cP |
| Kinematic viscosity at 20 °C: | 483 cSt |
| Kinematic viscosity at 40 °C: | >20,5 cSt |
| Concentration: | Non-applicable * |
| pH: | Non-applicable * |
| Vapour density at 20 °C: | Non-applicable * |
| Partition coefficient n-octanol/water 20 °C: | Non-applicable * |
| Solubility in water at 20 °C: | Non-applicable * |
| Solubility properties: | Immiscible |
| Decomposition temperature: | Non-applicable * |
| Melting point/freezing point: | Non-applicable * |
| Explosive properties: | Non-applicable * |
| Oxidising properties: | Non-applicable * |

Flammability:

| | |
|----------------------------|------------------|
| Flash Point: | 16 °C |
| Flammability (solid, gas): | Non-applicable * |
| Autoignition temperature: | 412 °C |
| Lower flammability limit: | 9,2 |
| Upper flammability limit: | 1,8 |

9.2 Other information:

| | |
|---------------------------|------------------|
| Surface tension at 20 °C: | Non-applicable * |
| Refraction index: | Non-applicable |

SECTION 10: STABILITY AND REACTIVITY**10.1 Reactivity:**

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

- CONTINUED ON NEXT PAGE -

**REPAINT**
Acrylic Flexible Paint**SECTION 10: STABILITY AND REACTIVITY (continued)****10.3 Possibility of hazardous reactions:**

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

| Shock and friction | Contact with air | Increase in temperature | Sunlight | Humidity |
|--------------------|------------------|-------------------------|---------------------|----------------|
| Not applicable | Not applicable | Risk of combustion | Avoid direct impact | Not applicable |

10.5 Incompatible materials:

| Acids | Water | Combustive materials | Combustible materials | Others |
|--------------------|----------------|----------------------|-----------------------|-------------------------------|
| Avoid strong acids | Not applicable | Avoid direct impact | Not applicable | Avoid alkalis or strong bases |

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION**11.1 Information on toxicological effects:**

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. With possibility of effects that are hazardous to the health, it is recommended not to breathe the vapours for long periods of time.

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

A.- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for inhalation. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Produces eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
- Cutaneous: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous with sensitising effects. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for inhalation. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- CONTINUED ON NEXT PAGE -

**REPAINT**
Acrylic Flexible Paint**SECTION 11: TOXICOLOGICAL INFORMATION (continued)**

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, however, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.

- Skin: Repeated exposure may cause skin dryness or cracking

H- Aspiration hazard:

Based on available data, the classification criteria are not met, however it does contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

| Identification | Acute toxicity | Genus |
|--|---|---|
| Ethylbenzene CAS: 100-41-4 EC: 202-849-4 | LD50 oral LD50 dermal LC50 inhalation | 3500 mg/kg 15354 mg/kg 17,2 mg/L (4 h) Rat Rabbit Rat |
| Xylene (mixture of isomers) CAS: 1330-20-7 EC: 215-535-7 | LD50 oral LD50 dermal LC50 inhalation | 2100 mg/kg 1100 mg/kg (ATEi) 11 mg/L (4 h) (ATEi) Rat Rat |
| 2-butanone CAS: 78-93-3 EC: 201-159-0 | LD50 oral LD50 dermal LC50 inhalation | 4000 mg/kg 6400 mg/kg 23,5 mg/L (4 h) Rat Rabbit Rat |
| 4-methylpentan-2-one CAS: 108-10-1 EC: 203-550-1 | LD50 oral LD50 dermal LC50 inhalation | 2080 mg/kg >2000 mg/kg 11 mg/L (4 h) (ATEi) |
| Butyl Acetate CAS: 123-86-4 EC: 204-658-1 | LD50 oral LD50 dermal LC50 inhalation | 12789 mg/kg 14112 mg/kg 23,4 mg/L (4 h) Rat Rabbit Rat |
| Fatty acids, C18, unsatd., dimers, reaction products with N,N-dimethyl-1,3-propanediamine and 1,3-propanediamine CAS: 162627-17-0 EC: Non-applicable | LD50 oral LD50 dermal LC50 inhalation | >2000 mg/kg >2000 mg/kg Non-applicable |
| 2-butoxyethanol CAS: 111-76-2 EC: 203-905-0 | LD50 oral LD50 dermal LC50 inhalation | 500 mg/kg 1100 mg/kg 11 mg/L (4 h) Rat Rat Rat |

Acute Toxicity Estimate (ATE mix):

| | ATE mix | Ingredient(s) of unknown toxicity |
|------------|---------------------------------------|-----------------------------------|
| Oral | >2000 mg/kg (Calculation method) | Non-applicable |
| Dermal | 3333,81 mg/kg (Calculation method) | 0 % |
| Inhalation | 22,44 mg/L (4 h) (Calculation method) | 0 % |

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

| Identification | Acute toxicity | Species | Genus |
|--|----------------------|---|--|
| Xylene (mixture of isomers) CAS: 1330-20-7 EC: 215-535-7 | LC50 EC50 EC50 | 13.5 mg/L (96 h) 0.6 mg/L (96 h) 10 mg/L (72 h) | Oncorhynchus mykiss Gammarus lacustris Skeletonema costatum Fish Crustacean Algae |
| 4-methylpentan-2-one CAS: 108-10-1 EC: 203-550-1 | LC50 EC50 EC50 | 900 mg/L (48 h) 862 mg/L (24 h) 980 mg/L (48 h) | Leuciscus idus Daphnia magna Scenedesmus subspicatus Fish Crustacean Algae |
| 2-butanone CAS: 78-93-3 EC: 201-159-0 | LC50 EC50 EC50 | 3220 mg/L (96 h) 5091 mg/L (48 h) 4300 mg/L (168 h) | Pimephales promelas Daphnia magna Scenedesmus quadricauda Fish Crustacean Algae |

- CONTINUED ON NEXT PAGE -

**REPAINT**
Acrylic Flexible Paint**SECTION 12: ECOLOGICAL INFORMATION (continued)**

| Identification | | Acute toxicity | | Species | Genus |
|-----------------|------|------------------|--|---------------------------------|------------|
| Ethylbenzene | LC50 | 42.3 mg/L (96 h) | | Pimephales promelas | Fish |
| CAS: 100-41-4 | EC50 | 75 mg/L (48 h) | | Daphnia magna | Crustacean |
| EC: 202-849-4 | EC50 | 63 mg/L (3 h) | | Chlorella vulgaris | Algae |
| Butyl Acetate | LC50 | 62 mg/L (96 h) | | Leuciscus idus | Fish |
| CAS: 123-86-4 | EC50 | 73 mg/L (24 h) | | Daphnia magna | Crustacean |
| EC: 204-658-1 | EC50 | 675 mg/L (72 h) | | Scenedesmus subspicatus | Algae |
| 2-butoxyethanol | LC50 | 1490 mg/L (96 h) | | Lepomis macrochirus | Fish |
| CAS: 111-76-2 | EC50 | 1815 mg/L (48 h) | | Daphnia magna | Crustacean |
| EC: 203-905-0 | EC50 | 911 mg/L (72 h) | | Pseudokirchneriella subcapitata | Algae |

12.2 Persistence and degradability:

| Identification | | Degradability | | Biodegradability | |
|----------------------|----------|----------------|-----------------|------------------|--|
| 4-methylpentan-2-one | BOD5 | 2.06 g O2/g | Concentration | 100 mg/L | |
| CAS: 108-10-1 | COD | 2.16 g O2/g | Period | 14 days | |
| EC: 203-550-1 | BOD5/COD | 0.95 | % Biodegradable | 84 % | |
| 2-butanone | BOD5 | 2.03 g O2/g | Concentration | Non-applicable | |
| CAS: 78-93-3 | COD | 2.31 g O2/g | Period | 20 days | |
| EC: 201-159-0 | BOD5/COD | 0.88 | % Biodegradable | 89 % | |
| Ethylbenzene | BOD5 | Non-applicable | Concentration | 100 mg/L | |
| CAS: 100-41-4 | COD | Non-applicable | Period | 14 days | |
| EC: 202-849-4 | BOD5/COD | Non-applicable | % Biodegradable | 90 % | |
| Butyl Acetate | BOD5 | Non-applicable | Concentration | Non-applicable | |
| CAS: 123-86-4 | COD | Non-applicable | Period | 5 days | |
| EC: 204-658-1 | BOD5/COD | 0.79 | % Biodegradable | 84 % | |
| 2-butoxyethanol | BOD5 | 0.71 g O2/g | Concentration | 100 mg/L | |
| CAS: 111-76-2 | COD | 2.2 g O2/g | Period | 14 days | |
| EC: 203-905-0 | BOD5/COD | 0.32 | % Biodegradable | 96 % | |

12.3 Bioaccumulative potential:

| Identification | | Bioaccumulation potential | |
|-----------------------------|-----------|---------------------------|--|
| Xylene (mixture of isomers) | BCF | 9 | |
| CAS: 1330-20-7 | Pow Log | 2.77 | |
| EC: 215-535-7 | Potential | Low | |
| 4-methylpentan-2-one | BCF | 2 | |
| CAS: 108-10-1 | Pow Log | 1.31 | |
| EC: 203-550-1 | Potential | Low | |
| 2-butanone | BCF | 3 | |
| CAS: 78-93-3 | Pow Log | 0.29 | |
| EC: 201-159-0 | Potential | Low | |
| Ethylbenzene | BCF | 1 | |
| CAS: 100-41-4 | Pow Log | 3.15 | |
| EC: 202-849-4 | Potential | Low | |
| Butyl Acetate | BCF | 4 | |
| CAS: 123-86-4 | Pow Log | 1.78 | |
| EC: 204-658-1 | Potential | Low | |
| 2-butoxyethanol | BCF | 3 | |
| CAS: 111-76-2 | Pow Log | 0.83 | |
| EC: 203-905-0 | Potential | Low | |

12.4 Mobility in soil:

| Identification | | Absorption/desorption | | Volatility | |
|-----------------------------|-----------------|-----------------------|------------|-------------------------------|--|
| Xylene (mixture of isomers) | Koc | 202 | Henry | 524,86 Pa·m ³ /mol | |
| CAS: 1330-20-7 | Conclusion | Moderate | Dry soil | Yes | |
| EC: 215-535-7 | Surface tension | Non-applicable | Moist soil | Yes | |

- CONTINUED ON NEXT PAGE -

**REPAINT**
Acrylic Flexible Paint

| Identification | Absorption/desorption | | | Volatility |
|--|-----------------------|----------------------|------------|---------------------------------|
| 4-methylpentan-2-one CAS: 108-10-1 EC: 203-550-1 | Koc | Non-applicable | Henry | Non-applicable |
| | Conclusion | Non-applicable | Dry soil | Non-applicable |
| | Surface tension | 2,35E-2 N/m (25 °C) | Moist soil | Non-applicable |
| 2-butanone CAS: 78-93-3 EC: 201-159-0 | Koc | 30 | Henry | 5,77 Pa·m ³ /mol |
| | Conclusion | Very High | Dry soil | Yes |
| | Surface tension | 2,396E-2 N/m (25 °C) | Moist soil | Yes |
| Ethylbenzene CAS: 100-41-4 EC: 202-849-4 | Koc | 520 | Henry | 798,44 Pa·m ³ /mol |
| | Conclusion | Moderate | Dry soil | Yes |
| | Surface tension | 2,859E-2 N/m (25 °C) | Moist soil | Yes |
| Butyl Acetate CAS: 123-86-4 EC: 204-658-1 | Koc | Non-applicable | Henry | Non-applicable |
| | Conclusion | Non-applicable | Dry soil | Non-applicable |
| | Surface tension | 2,478E-2 N/m (25 °C) | Moist soil | Non-applicable |
| 2-butoxyethanol CAS: 111-76-2 EC: 203-905-0 | Koc | 8 | Henry | 1,621E-1 Pa·m ³ /mol |
| | Conclusion | Very High | Dry soil | No |
| | Surface tension | 2,729E-2 N/m (25 °C) | Moist soil | Yes |

12.5 Results of PBT and vPvB assessment:

Non-applicable

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS**13.1 Waste treatment methods:**

| Code | Description | Waste class (Regulation (EU) No 1357/2014) |
|-----------|---|--|
| 08 01 11* | Waste paint and varnish containing organic solvents or other dangerous substances | Dangerous |

Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP4 Irritant — skin irritation and eye damage, HP6 Acute Toxicity

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) n°1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION ****Transport of dangerous goods by land:**

With regard to ADR 2015 and RID 2015:

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -

**REPAINT**
Acrylic Flexible Paint**SECTION 14: TRANSPORT INFORMATION ** (continued)**

| | |
|---|----------------|
| 14.1 UN number: | UN1263 |
| 14.2 UN proper shipping name: | PAINT |
| 14.3 Transport hazard class(es): | 3 |
| Labels: | - |
| 14.4 Packing group: | III |
| 14.5 Dangerous for the environment: | Non-applicable |
| 14.6 Special precautions for user | |
| Special regulations: | |
| Tunnel restriction code: | D/E |
| Physico-Chemical properties: | see section 9 |
| Limited quantities: | Non-Applicable |
| 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code: | Non-applicable |

Transport of dangerous goods by sea:

With regard to IMDG 37-14:

| | |
|---|----------------|
| 14.1 UN number: | UN1263 |
| 14.2 UN proper shipping name: | PAINTS |
| 14.3 Transport hazard class(es): | 3 |
| Labels: | - |
| 14.4 Packing group: | III |
| 14.5 Dangerous for the environment: | Non-applicable |
| 14.6 Special precautions for user | |
| Special regulations: | |
| EmS Codes: | F-D, S-U |
| Physico-Chemical properties: | see section 9 |
| Limited quantities: | - |
| 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code: | Non-applicable |

Transport of dangerous goods by air:

With regard to IATA/ICAO 2015:

| | |
|---|----------------|
| 14.1 UN number: | UN1263 |
| 14.2 UN proper shipping name: | PAINT |
| 14.3 Transport hazard class(es): | 3 |
| Labels: | - |
| 14.4 Packing group: | III |
| 14.5 Dangerous for the environment: | Non-applicable |
| 14.6 Special precautions for user | |
| Physico-Chemical properties: | see section 9 |
| 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code: | Non-applicable |

*** Changes with regards to the previous version***SECTION 15: REGULATORY INFORMATION****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**

Candidate substances for authorisation under the Regulation (EC) 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) 1005/2009, about substances that deplete the ozone layer: Non-applicable

- CONTINUED ON NEXT PAGE -

**REPAINT**
Acrylic Flexible Paint**SECTION 15: REGULATORY INFORMATION (continued)**

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:

- metallic glitter intended mainly for decoration,
- artificial snow and frost,
- "whoopee" cushions,
- silly string aerosols,
- imitation excrement,
- horns for parties,
- decorative flakes and foams,
- artificial cobwebs,
- stink bombs.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as data used in a risk evaluation of the local circumstances in order to establish the necessary risk prevention measures for the manipulation, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION**Legislation related to safety data sheets:**

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) N° 1907/2006 (Regulation (EC) N° 2015/830)

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3):

- Removed Content

Solvent naphtha (petroleum), light arom. < 0.1 % EC 200-753-7 (64742-95-6)

TRANSPORT INFORMATION (SECTION 14):

- Packing group

Texts of the legislative phrases mentioned in section 2:

H315: Causes skin irritation

H225: Highly flammable liquid and vapour

H319: Causes serious eye irritation

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) n° 1272/2008:

Acute Tox. 4: H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled

Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled

Acute Tox. 4: H332 - Harmful if inhaled

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways

Eye Irrit. 2: H319 - Causes serious eye irritation

Flam. Liq. 2: H225 - Highly flammable liquid and vapour

Flam. Liq. 3: H226 - Flammable liquid and vapour

H280 – Contains pressurized gas. Risk of explosion in case of overheating

Skin Irrit. 2: H315 - Causes skin irritation

Skin Sens. 1: H317 - May cause an allergic skin reaction

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure

STOT SE 3: H335 - May cause respiratory irritation

STOT SE 3: H336 - May cause drowsiness or dizziness

Classification procedure:

Skin Irrit. 2: Calculation method

Flam. Liq. 2: Calculation method (2.6.4.3)

- CONTINUED ON NEXT PAGE -



REPAINT Acrylic Flexible Paint

SECTION 16: OTHER INFORMATION (continued)

Advice related to training:

Minimal training is recommended to prevent industrial risks for staff using this product, in order to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://esis.jrc.ec.europa.eu>

<http://echa.europa.eu>

<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5-day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50

Log-POW: Octanol–water partition coefficient

Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -